

SITEXCOLABEL

L20  
L30



RESEARCH AND DEVELOPMENT, S.L.  
C. Mosquerola, 88 · 17180 Vilablareix · Girona · SPAIN  
+34 972 396 735 · [sitexco@tegtechnologies.com](mailto:sitexco@tegtechnologies.com)  
[www.tegtechnologies.com](http://www.tegtechnologies.com)  
[www.sitexco.com](http://www.sitexco.com)



**SITEXCOLABEL**  
LASER CLEANER FOR ANILOX ROLLS

# SITEXCO LABEL

The Sitexco Label Anilox Cleaning System L20 / L30 is a laser system designed using the Sitexco PLUS innovative technology and it is specifically for narrow web printers.

- Incorporating Sitexco PLUS cutting-edge technology, it is the fastest, safest, and most cost-effective option available.
- Cleaning times are between 5 and 15 minutes.
- Improving print quality as well as production plan since the rollers continue to function as new.
- Removing gears and bearings is not necessary.
- Helping sustainability projects. It does not require water or the use of chemicals, producing no waste and reaching more efficiency in cleaning processes.
- It is still a compact machine that will deep clean any solvent, UV or water-based ink, adhesives, varnishes, and coatings.
- Sitexco laser cleaning technology is safe for the environment, safe for the operators and safe for the aniloxes.



Sitexco Label L20 / L30 is an evolution of the L10 system, which incorporates the improvements suggested by our customers, to supply a system that really meets the needs of the narrow web sector:

- ✓ Standardized SLP programs
- ✓ Focused and enhanced aspiration
- ✓ Multi-cleaning option
- ✓ Rear opening to facilitate maintenance operations

## TECHNICAL DATA

🕒 **Approximate cleaning time:** Depending on roller dimensions (between 5' and 15')

⚙️ **Operation:** Exceptionally simple

⚙️ **Optionals:** Not available / No dispense

⊕ **Accessories:** Supporting table

DIMENSIONS	L20	L30	TECHNICAL SPECIFICATIONS	L20	L30
<b>Length:</b>	1.235 mm / 48,62"	1.435 mm / 56,49"	<b>Maximum cleaning length:</b>	850 mm / 33,46"	1.000 mm / 39,37"
<b>Height:</b>	1.000 mm / 39,37"	1.000 mm / 39,37"	<b>Maximum length of the roller:</b>	1050 mm / 41,34"	1.200 mm / 47,24"
<b>Width:</b>	575 mm / 22,64"	575 mm / 22,64"	<b>Minimum diameter of the roller:</b>	35 mm / 1,38"	55 mm / 2,16"
<b>Weight:</b>	160 Kg / 353 lb	180 Kg / 397 lb	<b>Maximum diameter of the roller:</b>	140 mm / 5,52"	160 mm / 6,29"
			<b>Maximum weight of the roller:</b>	30 Kg / 66 lb	30 Kg / 66 lb